

SMART PRIMER ABS

Primer before the application of microcement for absorbent surfaces such as plasterboard or plaster.

Water-based acrylic dispersion. Its main function is to facilitate the union between the existing substrate and the new microcement, besides equalizing the absorption in all the substrate. It is presented ready to use for its application by brush or microfiber roller.

PROPERTIES

- Adherence promoter for absorbent substrates such as plasterboard or plaster.
- Can be applied by roller or brush in one coat.
- Water based, non flammable.
- Free of plasticizers, solvents, ammonia and free of emulsifiers.
- The product is supplied ready for use.

PREPARATION

Shake before use. Pour the product in the tray, wet the roller or brush and apply on the surface.

CONSUMPTION

On absorbent surfaces: 0.10 L/m²/coat

TECHNICAL DATA

Typology	Water-based acrylic dispersion
Appearance	Milky Liquid
pH	7
Viscosity	10 - 11 s (Copa Ford 4)
Density	1,01 ± 0.01 g/ml (a 20°C)
Drying by touch	30 min
Application temperature	From 5°C to 35°C

CHARACTERISTICS

- Water-based acrylic dispersion
- Solids: 10,4 %

APPLICATION

The substrate must be dry, clean and firm, free of grease or oil.

Apply a layer of Smart Primer ABS on the absorbent surface (such as plaster or plasterboard) by brush or microfiber roller.

Wait a minimum of 30 minutes to dry and no more than 24 hours to apply the first coat of microcement.

PACKAGING

It is supplied in 5L and 1L containers.

STORAGE CONDITIONS

The product must be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from heat sources and direct sunlight. The time of use is 1 year from the date of manufacture, properly stored.



The product must not be used for purposes other than those specified, without first having written instructions from its handling. It is always the user's responsibility to take the appropriate measures in order to comply with the requirements established in the legislation.

Product Safety Data Sheets are available for the professional.

SPECIAL PRECAUTIONS

In case of contact with the eyes, clean with plenty of water for 15 minutes.

In case of contact with skin wash with soap and water.

Do not ingest. In case of ingestion do not provoke vomiting and seek medical attention immediately.

It is recommended to comply with the following measures:

- Good ventilation.
- Protective glasses to avoid splashes.
- Rubber gloves.

Empty containers should be disposed of in accordance with current legislation. To prevent the product from drying out or thickening, close the lid after each use.

This product is not toxic, dangerous or flammable, under normal handling conditions. This product does not contain any harmful substances which, under the current regulation, entails taking any additional measures with regard to its labelling.

Keep out of reach of children.

CLEANING OF TOOLS

Tools are washed with water immediately after use. Once hardened, the material can only be removed by mechanical means.



Last edition: April 2021