

SMART PRIMER GRIP

SMART PRIMER GRIP is a ready-to-use aggregate adhesion promoter for indoor and outdoor use, without emission of volatile organic substances, based on synthetic resins in aqueous dispersion.

PROPERTIES

- Provides a rough surface ensuring an excellent adhesion on smooth substrates or low absorption.
- It is used for the application of microcement, plastering, laying tiles on a base of concrete, ceramics, hydraulic tiles...
- Can be applied by roller or brush in one coat.
- The product is supplied ready for use.

PREPARATION

Stir the product manually with a spatula to incorporate the aggregate.

Application material: 15 cm. roller.

CONSUMPTION

0,25 L/m², varying according to the porosity of the substrate.

TECHNICAL DATA

Type of polymer	Acrylic
Appearance	Granulated Milk Liquid
рН	Between 7,5 and 9
Apparent density	1,5 ± 0,05 g/cm³
Dry touch (239C)	3-4 h depending on the thickness applied.

FEATURES

- Indoor/outdoor acrylic resin and selected aggregates.
- Water based.
- Solids: 88 ± 2%.

APPLICATION

The support must be dry, clean, firm and free of grease or oil

Shake well before use and apply Smart Primer GRIP to the surface by brush or roller.

Wait between 2 and 4 hours to dry before applying the Smart Base microcement.

SPECIAL PRECAUTIONS

Non-flammable product.

In case of contact with skin wash with soap and water. Never use solvents or thinners. Do not ingest. In If swallowed, do not induce vomiting and seek attention medical immediately.

The following measures are recommended:

- Good ventilation.
- Protective glasses to avoid splashes.
- Rubber gloves.

Empty containers should be disposed of in accordance with the legal regulations in force. To prevent the product from drying out or thickening, close the cover after each use. This product is non-toxic, non-flammable and non-toxic in normal handling conditions.

This product does not contain any harmful substances that under the current regulation, to take any kind of additional measure in terms of labelling.

Keep out of reach of children.

PACKAGING

It is supplied in 2L containers.

STORAGE CONDITIONS

It should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from heat sources and direct sunlight. The time of use of the product is one year from its date of manufacture, provided it is properly stored.

CLEANING OF TOOLS

Tools are washed with water immediately after use.





The product must not be used for purposes other than those specified, without first having written instructions from its use. It is always the user's responsibility to take the appropriate measures in order to comply with the requirements established in the legislation. The Safety Data Sheets of the product are at the disposal of the professional.

Last updated: January 2021