



# SMART COVER TILES

## TILE PAINT

**SMARTCOVER TILES** is a coating designed for the renewal of ceramic surfaces, tiles, stoneware, mosaic, etc.

**SMARTCOVER TILES** offers good chemical resistance and can be used in bathrooms.  
Available in eleven colors with a satin finish.

### PROPERTIES

- Especially recommended for the renewal of vertical ceramic coatings.
- Good water resistance.
- Adheres without the need for priming on double-fired ceramics, single-fired ceramics, porcelain stoneware, mosaic, tiles, and wood panels while respecting the original texture.
- One-component product and ready to use. Remove the product before use.
- Easy application.

### USES / APPLICATION FIELDS

Product developed for the renovation of tiles with a decorative finish.

Tile paint designed for interiors. Maintenance: clean with a non-abrasive cloth dampened with water and neutral pH soap.

### TECHNICAL DATA

Color	11 colors available.
Finish	Satin
Hardness Persoz (s)	150 ± 5
Density	1,18 ± 0,02 g/cm <sup>3</sup>
Viscosity (H2 at 20 rpm)	3500 ± 1000 mPa•s
Minimum application temperature	10°C
Touch dry	30 min
Repainting	8h
Drying	24h
Curing time	7 days

### CHEMICAL RESISTANCES

SAMPLE SMARTCOVER TILES	APPLICATION DRYING TIME 7 DAYS
	CHEMICAL RESISTANCES FOR CONTACT OF 2H
WATER	5
SOAP	5
BLEACH	5
OIL	5
VINEGAR	5
WINE	3
AMMONIA	5
ALCOHOL	4

### CONSUMPTION

**SMARTCOVER TILES** : 0,15 L/m<sup>2</sup> (for 2 coats)

### FEATURES

- Water-based paint.
- Solids: 43 ± 2%

## SURFACE PREPARATION

Before painting, the surface must be properly prepared. It should be dry, clean, and free of dust, grease, or dirt. For a thorough cleaning, it is recommended to use our **SMART CLEANER** detergent cleaner.

In case the surface has been previously varnished or painted, it is necessary to check if it is in good condition and well-adhered. Otherwise, it is recommended to remove the previous coating. This can be done by sanding or stripping, ensuring to leave the surface in good condition. In case repair, consolidation, or joint sealing is required, proceed before applying **SMARTCOVER TILES**.

## SPECIAL PRECAUTIONS

For the cleaning and maintenance of surfaces painted with **SMARTCOVER TILES**, it is recommended to use neutral soaps and detergents or our **SMART CLEANER** diluted 1:10 in water.

Non-flammable product. In case of skin contact, wash with water and soap. Never use solvents or thinners. Do not ingest. In case of ingestion, do not induce vomiting and seek medical attention immediately.

It is recommended to comply with the following measures:

- Good ventilation.
- Use a mask with chemical absorbent.
- Protective glasses to avoid splashes.
- Rubber gloves.

Empty containers must be disposed of in accordance with current legal regulations.

To prevent the product from drying or thickening, close the lid after each use. Keep out of reach of children.

The product should not be used for purposes other than those specified without first having written instructions for its handling. It is always the responsibility of the user to take appropriate measures to comply with the requirements established in the legislation.

Safety Data Sheets for the product are available to professionals.

## APPLICATION

- Before applying **SMARTCOVER TILES**, ensure that the surface is dry and free from grease and dust. Remove the product before use.
- Apply with a brush or short-haired velour roller or microfiber roller.
- The application should be done at ambient temperatures between 10°C and 30°C.
- Apply one coat and wait for 8 hours before applying the second coat. If the coverage is not correct, apply a third coat (when applying a lighter paint color than the previous support tone and a contrast is perceived).
- Allow 7 days of drying time before use to achieve maximum performance.

## PACKAGING

It is available in 2.5L containers.

## CLEANING TOOLS

Tools should be washed with water immediately after use.

## STORAGE CONDITIONS

The product must be stored in its original closed container and protected from the elements at temperatures between 10°C and 30°C, in a dry and well-ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from the manufacturing date if stored properly.



**Last updated: January 2024**